WORK LIGHTS RANGE LED

ABL 500 LED SL

ABL 500 LED 850

ABL 500 LED 1200

ABL 500 LED 2000




















IIILED

Part Numbers	D14168	D14160	D14161	D14162
Bulb	12 LED	12 LED - 850 lumen	5 LED - 1200 lumen	6 LED - 2000 lumen
Lifetime	20 000 hours	20 000 hours	20 000 hours	20 000 hours
Color T°	6000K	6000K	6000K	6000K
Light Pattern	Flood	Flood	Flood	Flood
Consumption	6W	11W	20W	28W
Voltage	multi voltage 12-24V	multi voltage 12-24V	multi voltage 12-100V	multi voltage 12-100V
Connection	Built in DT 2 ways	Built in DT 2 ways	Built in DT 2 ways	Built in DT 2 ways
Water Tightness	IP68 - IP69K	IP68 - IP69K	IP68 - IP69K	IP68 - IP69K
Operating Temp [°]	- 40°C to +60°C	- 40°C to +85°C	- 40°C to +85°C	- 40°C to +85°C
Housing	Reinforced plastic alu insert	Aluminium	Aluminium	Aluminium
Lens	hardened glass lens	hardened glass lens	hardened glass lens	hardened glass lens
Mounting	pedestal - suspended	pedestal - suspended	pedestal - suspended	pedestal - suspended
Dimensions (mm)	101 x 97 x 47	102 x 98 x 80	102 x 98 x 80	102 x 98 x 80





Dalroad Bramingham Business Park, Enterprise Way, Luton, Bedfordshire, LU3 4BU T: 01582 505 252 | F: 01582 560 060 | W: www.dalroad.com | E: sales@dalroad.com

