

# Type : HV010 Series Relay

Revised : 2020-08-26  
 Issued : 2015-08-31



## ■ Type List

Terminal style	Contact form	Designation (provided with)	
		Flux tight	Flanged cover (Flux tight)
Plug-in terminal	1A (SPDM)	HV010-1AH-C	HV010-1AH-C1
PCB terminal		HV010P-1AH-C	-----

## ■ Ordering Information

HV010    P    -    1A    H    -    C      
 1        2        3        4        5        6.

- |   |   |
|---|---|
| 1. HV010 -- Basic series designation              | 4. H -- Contact material Ag alloy   |
| 2. Blank -- Plug-in terminal<br>P -- PCB terminal | 5. C -- Flux tight<br>C1 -- Flanged cover (Flux tight)  |
| 3. 1A -- Form A, single-pole, double-make (SPDM)  | 6. <input type="checkbox"/> -- Coil voltage (please refer to the coil rating data for the availability) |

## ■ Contact Rating

Rated load (Resistive)	10A 450VDC
------------------------	------------

## ■ Coil Rating (DC)

Rated voltage (V)	Rated current ±10 % at 23°C (mA)	Coil resistance ±10 % at 23°C (Ω)	Pick up Voltage (Max.) at 23°C	Drop out Voltage (Min.) at 23°C	Max. energize voltage at 23°C <sup>(1)</sup>	Max. coil energize duration	Power consumption at rated voltage
12	266	45	75% of rated voltage	5% of rated voltage	116% of rated voltage	180 sec.	approx. 3.2W

Notes : (1) Without contact load.

(2) Coil terminal with polarity sensitivity, please follow the layout instruction.

## ■ Specification

Contact material	Ag alloy
Voltage drop <sup>(1)</sup>	Typ.40mV at 10A
Operate time <sup>(1)</sup>	30ms Max.

## Type : HV010 Series Relay

Revised : 2020-08-26

Issued : 2015-08-31

Release time <sup>(1)</sup>	15ms Max.		
Insulation resistance <sup>(1)</sup>	100MΩ Min. (DC 500V)		
Dielectric strength <sup>(1)</sup>	Between open contact	: AC 2000V, 50/60Hz 1 min.	
	Between contact and coil	: AC 2500V, 50/60Hz 1 min.	
Vibration resistance	Operating extremes	10~500Hz, 5.0G	
	Damage limits	10~500Hz, 5.0G	
Shock resistance	Operating extremes	10G	
	Damage limits	100G	
Life expectancy	Mechanical		
	500,000 ops. (frequency 9000 ops./hr)		
	Electrical	Rated switching capacity (Resistive)	10A 450VDC: 50,000 ops. (frequency 180 ops./hr).
		Pre-charging simulation	100,000 ops. <sup>(14)</sup>
Overload switching capacity		12A 450VDC: 50 ops.	
Operating ambient temperature	-40 ~ +85°C (no freezing)		
Weight	Approx. 65g, 70g (flanged cover)		

Notes : (1) Initial value. Operate and release time excluding contact bounce.

(2) Coil and contact sides with polarities (+) and (-).

(3) Unless otherwise specified, all tests are under room temperature and humidity.

(4) Consider the heat of PCB is necessary, please check the actual condition of PCB.

(5) Applying no diode to this relay. The life expectancy will be lower when a diode is used. To use a varistor (ZNR) could absorb the coil surge of relay that is recommended.

(6) Do not use the relay exceeding the coil rating, contact rating and life expectancy, or this may cause the risk of overheating.

(7) To assure optimum performance, avoid the relay from dropping, hitting, or other unnecessary shocks.

(8) Take care to avoid cross connections as they may cause malfunctions or overheating.

(9) To avoid mounting the relay in strong magnetic fields (near a transformer or magnet) or close to an object that radiates heat.

(10) Use suitable harnesses and bus bars according to the current as below :

10A type : Min. 2 mm<sup>2</sup>

(11) To avoid unexpected damage, when tightening a screw, use no exceeding specified torque range as below :

M4 screw : 2.5 ~ 3 N.m

(12) Please pay attention to the phenomenon of freezing in the low temperature environment below 0°C. Please evaluate the actual use of the environment.

# Type : HV010 Series Relay

Revised : 2020-08-26


Issued : 2015-08-31

(13) Please contact Song Chuan for the detailed information.

(14) Pre-charging simulation circuit, please refer to figure 1.

Ex. Inrush 20A, break 3A ; ON 0.2s / OFF 1.8s.

◆ Figure 1



Confirmed by	Checked by	Prepared by
副總經理 葉家昇 20'.08.27	研發經理 蕭琪騰 20'.08.26	文管課長 胡麗珠 20'.08.26


# Type : HV010 Series Relay

Revised : 2020-08-26


Issued : 2015-08-31

## ■ Outline Dimensions

### ◆-C cover



### ◆-C1 cover




# Type : HV010 Series Relay

Revised : 2020-08-26


Issued : 2015-08-31

## ◆HV010P (-C cover type)



TOLERANCE:  
 LESS THAN: 1(0.039)±0.1(0.004)  
                   5(0.197)±0.3(0.012)  
                   20(0.787)±0.5(0.020)  
 MORE THAN:20(0.787)±1(0.039)

## ■ Wiring Diagram (Bottom view)



Load sides and coil terminals are with polarities (+) and (-).

## ■ PC Board Layout (Bottom view)

### ◆HV010P

