


D2.5/5.P.2L spring terminal blocks

Ground with 2 connections - 5 mm 0.197 in spacing




2.5 mm²
12 AWG



1SNA162029R0700

D2.5/5.P.2L



5 mm 0.197 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection:	Green-yellow	D2.5/5.P.2L	1SNA290029R0700	50	9.00


Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.12-4 mm ²	26-12 AWG	26-12 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.12-2.5 mm ²			Wire stripping length	9.5 mm 0.37 in
	with insulated ferrule				Tool	Flat screwdriver Ø 3.5 mm Ø 0.138 in
	Gauge	A2				
Rated cross section		2.5 mm ²	12 AWG	12 AWG		
Rated short-time withstand current (1s)		300 A				
Protection		IP20	NEMA 1			



Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED5.2L	1SNA291061R2400	20	2.00
3 Circuit separators	Orange	SCD5.2L	1SNA291352R0400	20	2.20
4 Terminal block markers	White	RC510	1SNA231000R0700	1	5.20



D2.5/5.P.3L spring terminal blocks

Ground with 3 connections - 5 mm 0.197 in spacing




2.5 mm²

12 AWG



1SNA162103F0014

D2.5/5.P.3L



5 mm 0.197 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D2.5/5.P.3L	1SNA290039R0100	50	11.00

Main technical data

Connecting capacity		IEC	UL	CSA
1 conductor per clamp	Rigid - Solid / Stranded	0.12-4 mm ²	26-12 AWG	26-12 AWG
	Flexible with non insulated ferrule	0.12-2.5 mm ²		
	with insulated ferrule			
Gauge		A2		
Rated cross section		2.5 mm ²	12 AWG	12 AWG
Rated short-time withstand current (1s)		300 A		
Protection		IP20	NEMA 1	


Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		9.5 mm 0.37 in
Tool		Flat screwdriver Ø 3.5 mm Ø 0.138 in




Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED5.3L	1SNA291051R2200	20	1.90
3 Circuit separators	Orange	SCD5.3L	1SNA291362R0600	20	2.60
4 Terminal block markers	White	RC510	1SNA231000R0700	1	5.20




D2.5/5.P.4L spring terminal blocks

Ground with 4 connections - 5 mm 0.197 in spacing



1SNA162069F0014

D2.5/5.P.4L



5 mm 0.197 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D2.5/5.P.4L	1SNA290019R0500	50	12.00

Main technical data

Connecting capacity	IEC	UL	CSA
1 conductor per clamp	Rigid - Solid / Stranded	0.12-4 mm ²	26-12 AWG
	Flexible	0.12-2.5 mm ²	26-12 AWG
	with non insulated ferrule		
	with insulated ferrule		
Gauge	A2		
Rated cross section	2.5 mm ²	12 AWG	12 AWG
Rated short-time withstand current (1s)	300 A		
Protection	IP20	NEMA 1	


Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		9.5 mm 0.37 in
Tool		Flat screwdriver Ø 3.5 mm Ø 0.138 in



Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED5.4L	1SNA291041R2000	20	2.20
3 Circuit separators	Orange	SCD5.4L	1SNA291372R0000	20	2.90
4 Terminal block markers	White	RC510	1SNA231000R0700	1	5.20




D2.5/5.I.P.3L spring terminal blocks

Ground with 3 connections - 5 mm 0.197 in spacing



D2.5/5.I.P.3L



5 mm 0.197 in spacing

Description


- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D2.5/5.I.P.3L	1SNA399072R0300	50	11.00


Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.12-4 mm ²	26-12 AWG	26-14 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible	0.12-2.5 mm ²			Wire stripping length	9.5 mm 0.37 in
	with non insulated ferrule				Tool	Flat screwdriver Ø 3.5 mm Ø 0.138 in
with insulated ferrule						
Gauge		A2				
Rated cross section		2.5 mm ²	12 AWG	14 AWG		
Rated short-time withstand current (1s)		300 A				
Protection		IP20	NEMA 1			



Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED5.I.3L	1SNA290311R0600	20	2.10
3 Terminal block markers	White	RC510	1SNA231000R0700	1	5.20



D2.5/5.I.P.4L spring terminal blocks

Ground with 4 connections - 5 mm 0.197 in spacing



2.5 mm²
12 AWG

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details


Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D2.5/5.I.P.4L	1SNA399073R0400	50	12.00

Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.12-4 mm ²	26-12 AWG	26-14 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.12-2.5 mm ²			Wire stripping length	9.5 mm 0.37 in
	with insulated ferrule				Tool	Flat screwdriver Ø 3.5 mm Ø 0.138 in
	Gauge	A2				
Rated cross section		2.5 mm ²	12 AWG	14 AWG		
Rated short-time withstand current (1s)		300 A				
Protection		IP20	NEMA 1			



D2.5/5.I.P.4L




5 mm 0.197 in spacing




Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED5.I.3L	1SNA290311R0600	20	2.10
3 Terminal block markers	White	RC510	1SNA231000R0700	1	5.20




D4/6.P.2L spring terminal blocks

Ground with 2 connections - 6 mm 0.236 in spacing



D4/6.P.2L



6 mm 0.236 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce)
Ground Screwless rail connection	Green-yellow	D4/6.P.2L	1SNA290069R1700	50	12.00 g

Main technical data

Connecting capacity		IEC	UL	CSA
1 conductor per clamp	Rigid - Solid / Stranded	0.2-6 mm ²	24-10 AWG	24-10 AWG
	Flexible	0.2-4 mm ²		
	with non insulated ferrule			
	with insulated ferrule			
	Gauge	A4		
Rated cross section		4.0 mm ²	10 AWG	10 AWG
Rated short-time withstand current (1s)		480 A		
Protection		IP20	NEMA 1	


Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		11 mm 0.43 in
Tool		Flat screwdriver Ø 4 mm Ø 0.157 in




Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce)
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70 g
		BAM2	1SNA206351R1600	50	12.00 g
2 End sections	Grey	FED5.2L	1SNA291061R2400	20	2.00 g
3 Circuit separators	Orange	SCD5.2L	1SNA291352R0400	20	2.20 g
4 Terminal block markers	White	RC610	1SNA233000R0100	1	7.50 g




D4/6.P.3L spring terminal blocks

Ground with 3 connections - 6 mm 0.236 in spacing



1SNC162018R0014

D4/6.P.3L



6 mm 0.236 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection:	Green-yellow	D4/6.P.3L	1SNA290409R1200	50	11.00

Main technical data

Connecting capacity	IEC	UL	CSA
1 conductor per clamp	Rigid - Solid / Stranded	0.2-6 mm ²	24-10 AWG
	Flexible	0.2-4 mm ²	24-10 AWG
	with non insulated ferrule		
	with insulated ferrule		
	Gauge	A4	
Rated cross section	4.0 mm ²	10 AWG	10 AWG
Rated short-time withstand current (1s)	480 A		
Protection	IP20	NEMA 1	


Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		11 mm 0.43 in
Tool		Flat screwdriver Ø 4 mm Ø 0.157 in




Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED6.3L	1SNA291694R2400	20	2.50
3 Terminal block markers	White	RC610	1SNA233000R0100	1	7.50




D4/6.P.4L spring terminal blocks

Ground with 4 connections - 6 mm 0.236 in spacing



1SNC162056F001.4

D4/6.P.4L



6 mm 0.236 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details


Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D4/6.P.4L	1SNA290414R2600	50	14.00

Main technical data

Connecting capacity		IEC	UL	CSA
1 conductor per clamp	Rigid - Solid / Stranded	0.2-6 mm ²	24-10 AWG	24-10 AWG
	Flexible with non insulated ferrule	0.2-4 mm ²		
	with insulated ferrule			
Gauge		A4		
Rated cross section		4.0 mm ²	10 AWG	10 AWG
Rated short-time withstand current (1s)		480 A		
Protection		IP20	NEMA 1	

Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		11 mm 0.43 in
Tool		Flat screwdriver Ø 4 mm Ø 0.157 in




Accessories


Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED6.4L	1SNA291696R2600	20	2.85
3 Terminal block markers	White	RC610	1SNA233000R0100	1	7.50

D6/8.P.2L spring terminal blocks

Ground with 2 connections - 8 mm 0.315 in spacing



D6/8.P.2L



8 mm 0.315 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground	Screwless rail connection: Green-yellow	D6/8.P.2L	1SNA290089R0400	50	16.00


Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.5-10 mm ²	22-8 AWG	22-8 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.5-6 mm ²			Wire stripping length	12.5 mm 0.49 in
	with insulated ferrule				Tool	Flat screwdriver Ø 5.5 mm Ø 0.217 in
Gauge		A5				
Rated cross section		6.0 mm ²	8 AWG	8 AWG		
Rated short-time withstand current (1s)		720 A				
Protection		IP20	NEMA 1			




Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED8.2L	1SNA291161R2500	20	2.00
3 Terminal block markers	White	RC810	1SNA234000R0200	1	8.20




D6/8.P.3L spring terminal blocks

Ground with 3 connections - 8 mm 0.315 in spacing



D6/8.P.3L



8 mm 0.315 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.


Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D6/8.P.3L	1SNA290422R2600	30	20.80

Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.5-10 mm ²	20-8 AWG	22-8 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.5-6 mm ²			Wire stripping length	11 mm 0.42 in
	with insulated ferrule				Tool	Flat screwdriver Ø 5.5 mm Ø 0.217 in
	Gauge	A5				
Rated cross section		6.0 mm ²	8 AWG	8 AWG		
Rated short-time withstand current (1s)		720 A				
Protection		IP20	NEMA 1			

RoHS	UL US	CSA	Gost R						
------	-------	-----	--------	--	--	--	--	--	--



Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	9 mm 0.354 in	BADL	1SNA399903R0200	50 4.70
		10 mm 0.394 in	BAM2	1SNA206351R1600	50 12.00
2 End sections	Grey	FED8.3L	1SNA291711R2400	20 3.40	
3 Terminal block markers	White	RC810	1SNA234000R0200	1 8.20	

D10/10.1.P.2L spring terminal blocks

Ground with 2 connections - 10 mm 0.394 in spacing



Description



- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection:	Green-yellow	D10/10.1.P.2L	1SNA290309R2500	25	28.00

Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.5-16 mm ²	20-6 AWG	20-6 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.5-10 mm ²			Wire stripping length	12 mm 0.47 in
	with insulated ferrule				Tool	Flat screwdriver Ø 5.5 mm Ø 0.217 in
	Gauge	B6				
Rated cross section		10.0 mm ²	6 AWG	6 AWG		
Rated short-time withstand current (1s)		1200 A				
Protection		IP20	NEMA 1			




10 mm 0.394 in spacing




Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED10.2L	1SNA291461R2200	20	4.10
3 Jumper bars	Orange	BJDL1.10.2	1SNA291472R2500	50	2.45
4 Terminal block markers	White	RC1010	1SNA238000R1600	1	1.30




D10/10.P.3L spring terminal blocks

Ground with 3 connections - 10 mm 0.394 in spacing



D10/10.P.3L



10 mm 0.394 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details


Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D10/10.P.3L	1SNA290427R2300	25	40.00

Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.5-16 mm ²	20-6 AWG	22-8 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.5-10 mm ²			Wire stripping length	12 mm 0.47 in
	with insulated ferrule				Tool	Flat screwdriver Ø 5.5 mm Ø 0.217 in
	Gauge	B6				
Rated cross section		10.0 mm ²	6 AWG	8 AWG		
Rated short-time withstand current (1s)		1200 A				
Protection		IP20	NEMA 1			



Accessories




Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	9 mm 0.354 in	BADL	1SNA399903R0200	50 4.70
		10 mm 0.394 in	BAM2	1SNA206351R1600	50 12.00
2 End sections	Grey	FED10.3L	1SNA291731R2000	20 4.00	
3 Jumper bars	Orange	BJDL1.10.2	1SNA291472R2500	50 2.45	
4 Terminal block markers	White	RC1010	1SNA238000R1600	1 1.30	

D16/12.P.2L spring terminal blocks

Ground with 2 connections - 12 mm 0.472 in spacing




16 mm²
6 AWG



1SNA1620/5F0014

D16/12.P.2L



12 mm 0.472 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection:	Green-yellow	D16/12.P.2L	1SNA399584R2200	25	56.00


Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.5-25 mm ²	20-6 AWG	20-4 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.5-16 mm ²			Wire stripping length	19 mm 0.73 in
	with insulated ferrule				Tool	Flat screwdriver Ø 6.5 mm Ø 0.256 in
	Gauge	A7				
Rated cross section		16.0 mm ²	6 AWG	4 AWG		
Rated short-time withstand current (1s)		1920 A				
Protection		IP20	NEMA 1			




Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADL	1SNA399903R0200	50	4.70
		BAM2	1SNA206351R1600	50	12.00
2 End sections	Grey	FED12.2L	1SNA399571R0400	10	5.00
3 Jumper bars	Orange	BJDL12-2	1SNA399563R0400	25	7.00
4 Terminal block markers	White	RC1010	1SNA238000R1600	1	1.30




D16/12.P.3L spring terminal blocks

Ground with 3 connections - 12 mm 0.472 in spacing



D16/12.P.3L



12 mm 0.472 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details


Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D16/12.P.3L	1SNA290432R2000	10	72.00

Main technical data

Connecting capacity		IEC	UL	CSA	Mounting instructions	
1 conductor per clamp	Rigid - Solid / Stranded	0.5-25 mm ²		20-4 AWG	Rail	TH 35-7.5, TH 35-15
	Flexible with non insulated ferrule	0.5-16 mm ²			Wire stripping length	19 mm 0.72 in
	with insulated ferrule				Tool	Flat screwdriver Ø 6.5 mm Ø 0.256 in
	Gauge	A7				
Rated cross section		16.0 mm ²		4 AWG		
Rated short-time withstand current (1s)		1920 A				
Protection		IP20	NEMA1			



Accessories



Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	9 mm 0.354 in	BADL	1SNA399903R0200	50 4.70
		10 mm 0.394 in	BAM2	1SNA206351R1600	50 12.00
2 End sections	Grey	FED12.3L	1SNA291721R2600	20 5.50	
3 Jumper bars	Orange	BJDL12-2	1SNA399563R0400	25 7.00	
4 Terminal block markers	White	RC1010	1SNA238000R1600	1 1.30	

D35/16.P.2L spring terminal blocks

Ground with 2 connections - 16 mm 0.630 in spacing




35 mm²
2 AWG



1SNC162077P0014

D35/16.P.2L



16 mm 0.630 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection:	Green-yellow	D35/16.P.2L	1SNA399620R1100	10	120.00

Main technical data

Connecting capacity	IEC	UL	CSA	Rail	TH 35-7.5, TH 35-15
1 conductor per clamp	Rigid - Solid / Stranded	2.5-50 mm ²		Wire stripping length	26 mm 1.02 in
	Flexible with non insulated ferrule with insulated ferrule	2.5-35 mm ²			
	Gauge	A9		Tool	Flat screwdriver Ø 6.5 mm Ø 0.256 in
Rated cross section	35.0 mm ²				
Rated short-time withstand current (1s)	4200 A				
Protection	IP20	NEMA 1			

RoHS		RoHS		Gost R						
------	--	------	--	--------	--	--	--	--	--	--

Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops 12 mm 0.472 in	Grey	BADH	1SNA116900R2700	50	24.00
2 Jumper bars 2 poles 115 A	Orange	BJDL16-2	1SNA399621R0600	25	10.00
3 Terminal block markers Blank card	White	RC1010	1SNA238000R1600	1	1.30

